


BREAK SHARP CORNERS MAY BE EITHER CHAMFER OR RADIUS FROM 0.2 mm MIN. TO 1.0 mm MAX.

THIS DRAWING IS A SOLE PROPERTY OF M & M Ltd. IT SHOULD NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT THEIR CONSENT

REFER DRAWING :- 008033351U91

REF PART NO: 007537394C91

UNSPECIFIED TOLERANCES FOR PART		SURFACE FINISH SYMBOLS:ISO-1302		 MAHINDRA & MAHINDRA LTD. FARM DIVISION, INDIA						
FORMING TO FORMING	UPTO 500 ±0.5 ABOVE 500 ±0.8	WELDING SYMBOLS:IS813								
CD BETWEEN HOLES	IN ONE PLANE ±0.2 IN DIFF PLANES±0.5	REMOVE ALL SHARP CORNERS & BURRS								
FORM TO PIERCE	±0.5	DO NOT SCALE ALL DIMENSIONS ARE IN mm	<SC> COUNT : 0		NAME	DATE	PROJECT CODE:			
HOLE SIZES	+0.2/-0		<CC> COUNT↙: 0		DSNR	AR	30-05-2023	ER NUMBER: ER23C0000228		
SLOT SIZES	±0.8		WEIGHT(kg) : 0.09		CHKR	NVC	30-05-2023	DESCRIPTION :		
FLANGE WIDTH	+1.0/-0.7		S/F AREA(cm²): 36		APPR	DS	30-05-2023	RATCHET BRAKE		
JOGGLE DEPTH	+0.3/0		MATERIAL:					PART NUMBER :		CL:
UNSPECIFIED TOLERANCES FOR PART & ASSEMBLY			EN8/EN9 AS PER BS970					008032997U01		NA
GENERAL TOLERANCES	UP TO 300 ±0.8 ABOVE 300 ±1.0				DWG.SIZE : A4		SCALE :		1:1	SHEET: 1 OF 1
ANGULAR TOLERANCE	±1°									